
6 TON **AIR-OPERATED ROLL LEAF** STAMPING PRESS

The 56 is a new design to replace the 4 and 6 ton Kensol 60 press. This medium-high pressure range, cast iron. C frame toggle machine utilizes one main air cylinder running down the center of the casting to eliminate frame twist. The 56 has a deep throat, yet can stamp items up to 6 inches high. Higher parts can be accommodated on the Kensol 156 (over).




FEATURING

· Cast iron, dimensionally stable, C frame construction

...Double toggle head drive automatically compensates for thickness variations

- · 3 inch head stroke for ease of feeding
- Accepts items up to 6 inches high
- · Ground steel work table slides out when makeready is required
- Electrical control panel with plug-in solid state heat controller and electronic dwell timer
- Setup switch on control panel
- Hand lever included to bring head down manually for setup, if desired
- OSHA approved two hand switches
- · Air filter, pressure regulator and automatic lubricator included
- Multiple feed roll leaf attachments available
- Both head and roll leaf attachment have adjustable speed valves
- Delay valve on roll leaf feed aids stripping action

SPECIFICATIONS



IMPRESSION AREA HEATING SYSTEM 6 x 8 inches 1,000 Watts

6 x 12 Inches 1,500 Watts 9 x 12 Inches 2,100 Watts 10 x 15 Inches 4,200 Watts 12 x 18 Inches 4,800 Watts

HEAD STROKE: 3 Inches DEPTH OF THROAT: 9 Inches MAXIMUM OPENING: 9 Inches WILL HOT STAMP ITEMS UP TO 6 INCHES HIGH

WORK TABLE:

%" x 12" x 14" standard on 6" x 8" and 6" x 12" heads 1" x 18" x 18" standard on 9" x 12" and 10" x 15" heads 1" x 16" x 24" standard on 12" x 18" head

Slide-out manually for ease of makeready
HEAT CONTROL: Plug-in style solid state 0-600°F range proportioning over 4200 watts

DWELL CONTROL: Plug-in style solid state electronic 0-5 second range, 0-10 second optional

CONTROLS: Two hand, concurrent, no tie down switches with head shut safety system

ELECTRICAL REQUIREMENTS: 110 Volts A.C. standard on 6" x 8" and 6" x 12" heads; 220 Volts A.C. standard on 9" x 12", 10" x 15" and 12" x 18" heads

COMPRESSED AIR REQUIREMENTS: 9 CFM at 80 P.S.I. DIMENSIONS: 40" deep x 30" wide x 40" high WEIGHT: 550 pounds net

See Bulletin 1-7 for type and die holders, turntable, power sliding table, and other accessories

KENSOL-OLSENMARK INC.

40 MELVILLE PARK ROAD, MELVILLE, N.Y. 11747 PHONE: (516) 694-7773 • TWX 510-224-6418

WE ALSO MANUFACTURE FOILMARK ROLL LEAF